

SMART ECOTARD MF

Environmentally friendly Mould & Form Face Retarder

PRODUCT DESCRIPTION

A transparent aqueous composition with a gel consistency colour tinted to assist application.

BENEFITS

- Excellent non-slump properties for application to vertical surface.
- Adheres well to treated surface after water carrier has evaporated.
- Suitable for application to all types of mould and formwork surfaces.

APPLICATION

- After long storage period lightly stir material to ensure uniform consistency.
- Ensure surface to be treated is clean, dry and free of any deposits.
- Apply uniformly by brush or roller at up to 4 sq.mts per litre.
- When placing concrete take precautions to ensure heavy scouring action does not remove the retarder.
- Removal of cement matrix should be as soon as possible after stripping and generally within 1-2 days after placing concrete.
- It should be carried out by low pressure water jetting and brooming or wire brushing in two directions at right angles to each other.

HEALTH & SAFETY

When working with Ecotard MF suitable protective clothing, eye/face protection and gloves should be worn.

TECHNICAL DATA

Colour	Blue.
Coverage	3-4 sq.mts per litre.
Packaging	25 litre bucket
Storage	Protect from frost. Keep containers sealed after use.
Shelf Life	1 year in sealed container when stored as recommended.

IMPORTANT NOTE

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.